

Model Information



■ Main Features

- Controls 4 USB 2.0 devices located in the LAN
- Auto-detecting 10/100Mbps Ethernet interface
- Driver automatically finds USB servers on LAN
- Supports Windows XP, Vista, 7 to 8.1
- Protocols TCP/IP, UDP, HTTP, DHCP, ICMP, DNS
- Administration Software

[Contact Online...](#)

NetUSB-400i

Quick Link: | [Main Features](#) | [More Pictures](#) | [Overview](#) | [Application](#) | [Hardware](#) | [Interface](#) | [Performance](#) | [Power and Environment](#) | [Special Features](#) | [Ordering Information](#) | [Optional Accessories](#) |

■ More Pictures



Click on the thumbnails for the large picture ...

[>Back to top](#)

■ Overview

The NetUSB-400i controls four USB 2.0 devices via Ethernet. The four USB ports on NetUSB-400i are seen as installed in the Windows PC. Devices connected to the ports are detected via Plug&Play. Several PC may use the same devices on a time-sharing base.

USB printers offer an automatic sharing option, to connect them when data is printed. Other PC use the same printer as soon as the previous job has finished printing.

The metal case and the flexible power supply make the NetUSB-400i a good choice in rough office and industrial environments.

■ Application

- Print server
- Automatic warehouse control system
- Retail system
- Remote surveillance
- Building automation system
- Other remote USB devices control

■ Hardware

Processor	ARM 9 170 Mhz
Memory	32MB SDRAM, 8 MB Flash
Connector type	USB type A Port RJ45 for Ethernet

[>Back to top](#)

■ Interface

Ethernet interface	Auto-detecting 10BaseT/100BaseTx
Protocols	TCP/IP, UDP, DHCP, ICMP, HTTP, DNS
USB interface	USB 2.0 High Speed
No. of port	4
No. of devices	4
Available Modes	Bulk transfer Isochronous transfer

[>Back to top](#)

■ Performance

Speed	Up to 480Mbps
--------------	---------------

IRQ	None
I/O address	None
>Back to top	
■ Power and Environment	
Power requirements	9 - 30V DC, 1.2A @ 12V
Dimension	127×92×27 mm ³ (W×L×H)
Operating Temp	0°C - 55°C
Storage Temp	-20°C - 85°
Case	SECC sheet metal (1mm)
Weight	300 g
>Back to top	
■ Special Features	
Installation	Administration utility automatically finds USB servers in the network
Configuration	Configuration over Driver Panels, WEB Browser
DNS	Domain Name Server support
Firmware	Firmware update over Administration Software and WEB Browser
LEDs	LEDs for Power, Ready, Ethernet Link/Speed, USB usage
>Back to top	
■ Ordering Information	
Part Number	413
Product Name	NetUSB-400i
Packing list	NetUSB-400i Power adapter CD-ROM with Driver and Configuration Software
>Back to top	
■ Optional Accessories	
662	DK 35A DIN-Rail mounting kit
>Back to top	

- * Specifications are subject to change without notice.
- * All trademarks and brands are property of their rightful owners.

NetUSB-400i

[>Back](#)



(2017 Jul 21)