

Model Information



■ Main Features

- Can control 1x RS232 devices located virtually anywhere (via Ethernet or Internet)
- Serial port DB9 male
- LAN interface 10BaseT/100BaseTx Ethernet
- Driver automatically finds NetCom devices in the network
- Configuration over Driver Panels, serial Port, Telnet, WEB Browser, SNMP
- Automatic mode switching between Driver and RAW Mode
- Support TCP/IP, UDP, Telnet, DHCP, ICMP, HTTP, SNMP V1/2c/3, DNS

[Contact Online...](#)

NetCom 111

(**Replaced by** [NetCom Plus 111](#))

Quick Link: | [Main Features](#) | [More Pictures](#) | [Overview](#) | [Application](#) | [Hardware](#) | [Interface](#) | [Performance](#) | [Operating Modes](#) | [Power and Environment](#) | [Special Features](#) | [Security](#) | [Ordering Information](#) | [Optional Accessories](#) |

■ More Pictures



Click on the thumbnails for the large picture ...

[>Back to top](#)

■ Overview

NetCom 111 is an industrial-strength network-based serial device server for connecting one RS232 device like CNC, PLC, weighting scale, scanner and other devices directly to the 10/100Mbps Ethernet network running TCP/IP.

In addition to allowing serial devices to get networked, any host (PC Server or Workstation) without network access can also access remote serial device via adding NetCom devices to the existing serial port. NetCom 111 can be configured over Driver Panels, WEB Browser, serial Port, Telnet, SNMP and serves as a transparent serial channel without platform and distance limitation.

New: The serial connector is pin-compatible to Com1 on a PC, as DB9 male. The RS232 Null-Modem Adapter is no longer required.

The power consumption of NetCom 111 is very low, supply via Ethernet is available. See [the option](#), read [background information](#), or check an [adapter](#).

■ Application

- | | |
|--|---|
| ■ Industrial / Factory / Laboratory automation | ■ SCADA system |
| ■ Automatic warehouse control system | ■ Building automation system |
| ■ Wafer fabrication system | ■ Self-service banking system |
| ■ Retail system | ■ Other remote and distributed serial devices control |

■ Hardware

Processor	ARM 7 TDMI 50MHz
I/O controller	16C550C or compatible
Memory	8MB SDRAM, 1 MB Flash
Connector type	RJ45 for LAN, DSUB 9 female for serial Port

[>Back to top](#)

■ Interface

LAN interface	Auto-detecting 10BaseT/100BaseTx
Protocols	TCP/IP, UDP, Telnet, DHCP, ICMP, HTTP, SNMP V1/2c/3, DNS
Serial interface	RS232 New: Connector DB9 male, not female
No. of port	1, Speed up to 460Kbps
Available Modes	RS232 full duplex
Signals	TxD,RxD, RTS,CTS, DTR,DSR, DCD, RI, GND

[>Back to top](#)

■ Performance

Speed	up to 460Kbps
Parity	None, even, odd, space, mark
Data bits	5, 6, 7, 8
Stop bits	1, 1.5, 2
IRQ	None
I/O address	None

[>Back to top](#)

■ Operating Modes

Driver Mode	VScom Driver for Windows NT 4.0, 2000 up to 7, Server 2000 up to 2008 R2, both x86 and x64 Editions. The Driver creates a virtual Com port, using Vscom NetCom protocol.
TCP Raw Server	Raw data transfer over TCP/IP. Accepts multiple incoming connections.
TCP Raw Client	Raw data transfer over TCP/IP. Connects to multiple hosts or devices waiting for incoming connections.
TCP Advanced Settings	Special settings for user-defined modes.
UDP Mode	Raw data transfer by UDP. The NetCom is client and server at the same time. With the timeout functionality and a configurable trigger string it can make defined UDP packets of incoming data.
Null Modem Tunnel	Connecting two NetCom used as virtual null modem cable.
IP Modem	The serial port emulates a standard modem. Operates by AT-commands, and dials to IP-Addresses instead of phone numbers. Windows "INF"-Driver provided for installation.
Print Server	The NetCom accepts print jobs, and spools them to the attached serial printer. Operates as of RFC1197, similar to the line printer daemon in Unix-systems

[>Back to top](#)

■ Power and Environment

Power requirements	9 - 30V DC, 200mA @ 12V
Power supply Adapter	12V DC 1A
Dimension	73×115×27 mm ³ (W×L×H) 101×121×27 mm ³ with DB9 connector and ears
Operating Temp	0°C - 60°C
Storage Temp	-20°C - 85°C
Case	SECC sheet metal (1mm)
Weight	0.2kg

[>Back to top](#)

■ Special Features

Installation	Configuration utility automatically finds NetCom devices in the network
---------------------	---

Operating mode	Automatic mode switching between Driver and TCP RAW mode. With TCP Advanced settings it is possible to configure the NetCom for using it in multiple modes, so it decides automatically which mode should be used.
Configuration	Configuration over Driver Panels, NetCom Manager, WEB Browser, serial console, Telnet, SNMP
SNMP	special VScom MIB included
ART	no
DNS	Domain Name Server support
Firewall	Special precautions for Firewall environments
Firmware	Firmware update over WEB Browser, Telnet, ComPort
LEDs	LEDs for Power, Tx, Rx, LAN Link, LAN Speed

[>Back to top](#)

■ Security

Password access	Every capabilities of configuration use the same password including SNMP V3
------------------------	---

[>Back to top](#)

■ Ordering Information

Part Number	664
Product Name	NetCom 111
Option PoE	Power supply over Ethernet, see NetCom 111-POE
Packing list	NetCom 111 Power supply adapter 12V, 1A CD-ROM with Driver and configuration software Printed Quick Installation Guide

[>Back to top](#)

■ Optional Accessories

662	DK 35A DIN-Rail mounting adapters
Serial Adapter	RS232 Null-Modem adapter, change male to female
VS-POE 10	Power over Ethernet Splitter, IEEE 802.3af compliant (15W max.)

[>Back to top](#)

* Specifications are subject to change without notice.

* All trademarks and brands are property of their rightful owners.

NetCom 111
[>Back](#)



Front and Back
[>Back](#)



New serial connector DB9 male

[>Back](#)



(2017 Jul 21)