


Model Information



■ Main Features

- PCI Express x1
- 2x RS232, RS422/485
- RS485 ART (Automatic Receive Transmit control)
- RS485 in 3 operation modes
- Compact board size (half-size)
- Built-in termination resistors
- Drivers for Windows 2000 to 7/2008R2

[Contact Online...](#)

VScom 200Ei PCIex

Quick Link: | [Main Features](#) | [More Pictures](#) | [Overview](#) | [Hardware](#) | [Interface](#) | [Performance](#) | [Configuration](#) | [Available modes](#) | [Power and Environment](#) | [Operating Systems supported](#) | [Ordering Information](#) |

■ More Pictures



Click on the thumbnails for the large picture ...

[>Back to top](#)

■ Overview

The VScom 200Ei PCIex is designed for RS232, RS422/485 industrial communication. It supports 2 independent RS232, RS422 or RS485 ports. Each port can be configured separate.

Available modes : RS232, RS422 full duplex

RS485 full duplex (4 wire)

RS485 half duplex (2 wire) with and without echo.

In RS485 modes applications enable transmission by simply sending data.

This is done by ART (Automatic Receive Transmit control) intelligence.

The Transmitter is disabled exactly with the end of the last character sent. No modification is necessary in programs.

In addition, hardware flow control and built-in termination resistors guarantee data integrity.

All of these features make VScom 200Ei PCIex suitable for harsh industrial applications.

Read the [News Article...](#)

■ Hardware

I/O controller	2x 16C950C, each with 128 bytes Tx/Rx FIFO
Connector type	Male DB9

[>Back to top](#)

■ Interface

Bus interface	PCI Express x 1
Serial interface	RS232, RS422 / 485
No. of ports	2

Signals	RS232 TxD, RxD, CTS, RTS, DTR, DSR, DCD, GND RS422 Tx+/-, Rx+/-, RTS+/-, CTS+/-, GND RS485 Data+/-, GND
RS485 data control	ART (Automatic Receive Transmit control)
Built-in termination resistor	RS422: 120 Ohm RS485: 120 Ohm, DIP enable / disable

[>Back to top](#)

■ Performance

Speed	RS232: up to 921.6Kbps RS422/485: up to 3.6Mbps
Max. no. of ports	Unlimited

[>Back to top](#)

■ Configuration

Parity	None, even, odd, space, mark
Data bits	5, 6, 7, 8
Stop bits	1, 1.5, 2
IRQ	Assigned by System
I/O address	Assigned by System

[>Back to top](#)

■ Available modes

RS232	full duplex
RS422	full duplex
RS485	4 wire , full duplex
RS485	2 wire, half duplex, with echo
RS485	2 wire, half duplex, without echo

[>Back to top](#)

■ Power and Environment

Power requirement	430mA max.(+5V)
Operation temp.	0°C - 55°C
Dimension	80mm x 59mm

[>Back to top](#)

■ Operating Systems supported

Windows XP up to 7	VScom high performance serial driver, x86 and x64 Editions
Server 2003 up to 2008 R2	VScom high performance serial driver, x86 and x64 Editions

[>Back to top](#)

■ Ordering Information


Part Number	4505
Product Name	VScom 200Ei PCIex
Packing list	VScom 200Ei PCIex card CD, English documentation

[>Back to top](#)

* Specifications are subject to change without notice.

* All trademarks and brands are property of their rightful owners.

VScom 200Ei PCIex
[>Back](#)



(2017 Jul 27)